

OTR Application Chart

WIDE BASE	TYRE SECTION (INCHES)	SECTION AIRBAG	INSIDE FLAT AIRBAG	INSIDE HEAT PAD		OUTSIDE HEAT PAD	EXTERNAL PACK WITH FLAT AIRBAG & STRAPS
				BIAS	RADIAL		
14.4-24 TO 16.9-38	13.00 TO 17.5	TR1315/20W FRB		MZ2519H	MZ3015H	TRZ2621H	TR2621E WITH TROC5XL STRAPS
18.4-34 TO 20.8-42	18.00 TO 21.00	M1721/24W FRB		MZ2519H OR MZ2626H	MZ3015H	TRZ2621H	TR2621E WITH TROC5XL STRAPS
23.1-26 TO 30.5-32	23.5 TO 26.5	M1721/24W FRB	M4824W	MZ2519H OR MZ2626H	MZ3015H	TRZ2621H	TR2621E WITH TROC5XL STRAPS
25/65-25	27.00 TO 29.5	M1721/24W FRB	M4824W M5432W*	MZ2519H OR MZ2626H	MZ3015H OR MZ4220H	TRZ2621H	TR2621E WITH TROC5XL STRAPS
35/65-33 TO 45/65-45	30.00 TO 37.5	M2732/32W	M5432W	MZ3132H OR MZ2626H	MZ4220H OR MZ4224H	MZ2626H OR MZ3132H	M4832E WITH M45/6/7 (1HG) 6 STRAPS
49.5/85-57 TO 50/65-51	40.00	M3842/32W		MZ3132H OR MZ2626H	MZ4220H OR MZ4224H OR MZ4824H OR MZ5224H	MZ2626H OR MZ3132H	M4832E WITH M45/6/7 (1HG) 6 STRAPS
46/90-57		M3842/32W	M5432W*				
50/80-57 TO 55/80-57		M4447/32W		MZ3132H OR MZ2626H	MZ4220H OR MZ4224H OR MZ4824H OR MZ5224H	MZ2626H OR MZ3132H	M4832E WITH M45/6/7 (1HG) 6 STRAPS
53/80R63 53.5/85-57 53.5/85-63 55.5/80-57 55.5/85-57 55.5/85-63		M4447/32W	M7532W OR M9032W	MZ3132H OR MZ2626H	MZ4220H OR MZ4224H OR MZ4824H OR MZ5224H	MZ2626H OR MZ3132H	M4832E WITH M45/6/7 (1HG) 6 STRAPS
59/80-63 60/80-57 70/70-57		M5054/32W	M9032W	MZ3132H OR MZ2626H	MZ4220H OR MZ4224H OR MZ4824H OR MZ5224H	MZ2626H OR MZ3132H	M4832E WITH M45/6/7 (1HG) 6 STRAPS

Please note that this Application Chart is a general guide for common tyre sizes. When selecting a Heat Pad, choose a size that will comfortably cover the largest patch that will be in used in that tyre range. This should be at least 3 or 4 inches over the patch dimensions in both orientations. Additional components are available. Please enquire at repair@monaflex.com

*When repairing 27.00" to 29.5" section widths in Bias tyres, it may be necessary to use a M5432W to fully cover the patch.
For certain brands of 46/90-57 tyres, it may be necessary to also use an M5432W inside Flat Airbag to fully fill the section void.